

CHIORINO[®]
1906


Passion for belting

**Your partner
for energy saving
and production safety**

Power transmission belts



T Series



Power transmission belts

You can choose from the Chiorino Thermoplastic power transmission belts for high speed machines, when your main goal is to reduce energy consumption, or you can decide for the robust and resilient Polyamide power transmission belts, especially known for their reliability and safety.

T-A

Aramid belt
with **CHIO-TPE™**
intermediate layer



KEY FEATURES

- Reduced energy consumption
- Highly flexible traction layer
- High Modulus of belt elasticity run at very low initial working tension
- Adhesive free jointing method
- Excellent service life

APPLICATION CRITERIA

- Suitable for long machines with limited take-up
- Low spindle rpm deviation from first to last spindle, leading to uniform yarn twist
- High transmittable power

T-E

Polyester belts
with **CHIO-TPE™**
intermediate layer



KEY FEATURES

- High longitudinal flexibility
- High modulus of belt elasticity
- High internal adhesion
- No rubber cracking
- Quiet Running
- Simple & easy installation
- Adhesive free jointing method
- Reduced energy consumption
- Long service life

APPLICATION CRITERIA

- Suitable for high speed machines with small pulley diameters and numerous reverse bendings
- Suitable for long machines with limited take-up
- Suitable for long, highspeed machines

T-E OE

Polyester belts
with **CHIO-TPE™**
intermediate layer



KEY FEATURES

- New advanced elastomer compound enabling an adequate rotor starting up time
- Proprietary thermoplastic interply, second generation of CHIO-TPE™ to deliver ideal flexibility
- Grinded surface, very high thickness tolerances minimizing rotor vibration

APPLICATION CRITERIA

- Suitable for high speed machines with small pulley diameters and numerous reverse bendings
- Suitable for long machines with limited take-up
- Suitable for long, highspeed machines

T HS

Polyamide belts
with **HS®** elastomer cover



KEY FEATURES

- Permanently Antistatic
- Excellent wear resistance
- Robust, resilient & dimensionally stable polyamide
- Long Service Life
- Resistant to oil
- High temperature resistance
- Low aging property of the HS® elastomer
- Constant coefficient of friction

APPLICATION CRITERIA

- Suitable for high mechanical stress
- Suitable for aggressive acceleration
- Suitable for extreme environments
- Suitable for short term overload

Technical data

Code	Type	Top and driving surface	Traction core	Perm. antist.	Total thicken.	Min. diam. ⁽¹⁾	K1% rel.	Temperature resistance		Carding	Draw frame	OE spinning	Ring spinning	TFO Spun yarn	TFO Filament	Draw textured Yarn	Covering	Overhead cleaner	Circular knitting
								mm	mm										

Thermoplastic belts with *CHIO-TPE* intermediate layer

T-A Aramid																				
CG-256	T60/30A	Elastomer	Aramid	•	3.00	80	60	-20	80											
T-E Polyester																				
CG-325	T25/20E	Elastomer	Polyester	•	2.00	25	17	-20	80	•	•		•							
CG-331	T25/25E	"	"	•	2.50	40	17	-20	80	•	•	•	•					•		
CG-329	T40/25E	"	"	•	2.50	50	18	-20	80			•						•		
CG-332	T40/30E	"	"	•	3.00	50	19	-20	80			•								
CG-328	T55/30E	"	"	•	3.00	50	25	-20	80			•	•					•		
T-E OE Polyester																				
CG-317	T40/26E-OE	Elastomer	Polyester	•	2.60	50	18	-20	80			•							•	

Polyamide belts with *HS* elastomer cover

CG-334	T0 HS	HS [®] Elastomer	Polyamide	•	1.40	20	2	-20	100												•	
CG-335	T1 HS	"	"	•	1.50	25	5	-20	100													•
CG-341	T1R HS	"	"	•	2.10	25	5	-20	100	•												•
CG-336	T2 HS	"	"	•	2.35	60	8	-20	100		•											•
CG-342	T2R HS	"	"	•	3.00	60	8	-20	100			•										•
CG-337	T3 HS	"	"	•	2.60	100	11	-20	100	•	•	•										•
CG-343	T3R HS	"	"	•	3.20	100	11	-20	100				•									•
CG-338	T4 HS	"	"	•	3.10	150	12.5	-20	100	•			•	•								•
CG-344	T4R HS	"	"	•	3.90	150	12.5	-20	100				•	•								•
CG-339	T6 HS	"	"	•	3.50	200	18	-20	100				•									•

(1) The diameter values listed here are dependent upon the running speed.
The data in this chart are valid under normal environmental conditions and are subject to change without notice.

Customer benefits

Thermoplastic belts with *CHIO-TPE*™ intermediate layer


Reduced energy consumption

Chiorino thermoplastic belts consume less energy compared with competitors thermoplastic belts, thanks to the highly flexible CHIO-TPE™ intermediate layer.



High temperature resistance

Chiorino thermoplastic belts provide a higher temperature resistance compared with competitor thermoplastic belts, thanks to the unique CHIO-TPE™ intermediate layer.



Reliable FASTJOINT

The FAST JOINT technology in combination with the new CHIO-TPE™ intermediate layer, enables easy on-site joining, high reliability and long service life.



Polyamide belts with *HS*® elastomer cover

High abrasion resistance

The unique HS® friction covers provide an excellent abrasion resistance and a uniform coefficient of friction over time.



Excellent resilience

The unique HS® elastomer offers outstanding resilience, high elasticity and crack resistance.



Long service life

Chiorino polyamide belts provide a long service life, thanks to the low aging property of the HS® covers.



CHIORINO AFFILIATED COMPANIES

America

CHIORINO AMERICA
Newark, DE
Tel. +1-302-292-1906
info@chiorino.us
www.chiorino.us

Australia

CHIORINO AUSTRALIA - Brisbane
Tel. +61-7-3274 1900
sales@chiorino.com.au
www.chiorino.com.au

Benelux

CHIORINO BENELUX B.V. - Utrecht,
The Netherlands
Tel. +31-30-2413060
chiorino@chiorino.nl
www.chiorino.nl

Byelorussia

CHIORINO-K - Minsk
Tel. +375-17-2804578
general@chiorino.ru
www.chiorino.ru

China

CHIORINO ASIA Ltd.
Hong Kong
Tel. +852-397-10818
info@chiorino.asia
www.chiorino.asia

CHIORINO LIAISON OFFICE, Shanghai
Tel. +86-21-37831019
info@chiorino.cn
www.chiorino.cn

France

CHIORINO SAS - Lagny, Paris
Tel. +33-1-64304075
chiorino.paris@chiorino.fr
www.chiorino.fr

Germany

CHIORINO GmbH - Mainz
Tel. +49-(0)6131-55449-0
info@chiorino.de
www.chiorino.de

Hungary

CHIORINO Kft. - Szigetszentmiklós,
Budapest
Tel. +36-24-525930
mail@chiorino.hu
www.chiorino.hu

India

CHIORINO INDIA - Salcete Goa
Tel. +918-322-782454
info@chiorino.in
www.chiorino.in

Italy

CHIORINO PARMA s.r.l. - Parma
Tel. +39-0521-292236
chiorinoparma@chiorino.com

CHIORINO VENETO s.r.l. - Colle Umberto
Tel. +39-0438-430460
chiorinoveneto@chiorino.com

Poland

CHIORINO Sp. z o.o. - Bydgoszcz
Tel. +48-(0)52-3487708
chiorino@chiorino.com.pl
www.chiorino.com.pl

Portugal

CHIORINO PORTUGAL, LDA
Alfena Valongo, Porto
Tel. +35-122-9684442
geral@chiorino.pt
www.chiorino.pt

Romania

CHIORINO srl - Cluj Napoca
Tel. +40-264-432977
chiorino@chiorino.ro
www.chiorino.ro

South Africa

CHIORINO SOUTH AFRICA (PTY) LTD.
Johannesburg
Tel. +27-11-3971268
sales@chiorino.co.za
www.chiorino.com

Spain

CHIORINO IBERICA S.A. - Rubí, Barcelona
Tel. +34-93-5860480
chiorino@chiorino.es
www.chiorino.es

Switzerland

CHIORINO SCHWEIZ GmbH - Wetzikon
Tel. +41-(0)43-3116001
info@chiorino.ch
www.chiorino.ch

United Kingdom

CHIORINO U.K. Ltd. - Featherstone
Tel. +44-1977-691880
sales@chiorino.co.uk
www.chiorino.co.uk

CHIORINO DISTRIBUTORS

Albania
Argentina
Armenia
Austria
Azerbaijan
Bangladesh
Belgium
Bolivia
Bosnia-Herzegovina
Botswana
Brazil
Bulgaria
Cambodia
Canada
Chile
Colombia
Costa Rica
Croatia
Cyprus
Czech Republic
Denmark
Egypt
Estonia
Fiji
Finland
Georgia
Greece
Guatemala
Honduras
Iceland
Indonesia
Iran
Ireland
Israel
Ivory Coast
Jordan
Kazakhstan
Kenya
Kyrgyzstan
Laos
Latvia
Lebanon
Lithuania
Macedonia
Malawi
Malaysia
Mexico
Moldova
Morocco
Myanmar
New Caledonia
New Zealand
Nicaragua
Pakistan
Panama
Papua New Guinea
Paraguay
Peru
Russia
Saudi Arabia
Serbia
Slovak Republic
Slovenia
South Korea
Sri Lanka
Sweden
Tajikistan
Thailand
Turkey
Turkmenistan
Ukraine
United Arab Emirates
Uzbekistan
Vietnam
Yemen
Zimbabwe

HEADQUARTERS AND PRODUCTION PLANTS

CHIORINO S.p.A.

Via S. Agata, 9
I-13900 Biella, Italy
Tel. +39 015 8489 1
Fax +39 015 849 61 61
chiorino@chiorino.com
www.chiorino.com

UNI EN ISO 9001:2015
UNI EN ISO 14001:2015
OHSAS 18001:2007
EMAS



ENGINEERING ADVICE
ON-SITE INSTALLATION SERVICE
AFTER SALES SUPPORT

